



TECHNICAL GASES AND DMW

CARBON DIOXIDE (liquid) - CO₂

DESCRIPTION

Under normal conditions carbon dioxide is a colorless, odorless gas, and of slightly sour taste. It is denser than air, inert, and non-combustible. It is liquefied at a pressure of 15 to 17 bar and temperature -30 to -35°C. CO₂ is not toxic and is present in the atmosphere at a concentration of about 0.03 vol. %. Higher concentrations are dangerous due to the reduction of oxygen in the air.

Belinka Perkemija produces liquid CO₂ to the quality required by the food industry.

APPLICATION OF CO₂

In food industry for:
freezing, aerating beverages, the manufacture and packaging of food in an inert atmosphere, decantation of beer, cooling of food during transport, water softening.

In foundry industry:
for hardening of foundry cores, for cleaning in steel processing, as a blowing gas in casting.

In chemical industry:
as a protective gas for chemical synthesis, as a neutralizing agent, for the production of carbonates, for supercritical extraction, for grinding of granules, for the production of hollow-blown plastic.

In biology and medicine:
as a means of extinguishing fires in electrical installations and various chemicals, as a coolant for various purposes.

PACKAGING

Carbon dioxide is delivered in the following packaging units:

- in bulk

IDENTIFICATION OF THE PRODUCT

Trade name: CARBON DIOXIDE, liquid

Substance name: CARBON DIOXIDE

IUPAC name: CARBON DIOXIDE

Molecular formula: CO₂

Molecular Mass: 44 g/mol

CAS No.: 124-38-9

EI NECS No.: 204-696-9

CUSTOMS TARIFF NO (HS CODES): XXXXX



HYDROGEN - H₂

DESCRIPTION

Belinka Perkemija produces hydrogen in the technological process of steam reforming (reaction between natural gas and steam). The production capacity for pure hydrogen is 225 kg/h.

The quality of hydrogen is (99.9 vol. %), since the majority of hydrogen is used in the production of hydrogen peroxide where almost 100% purity is required.

APPLICATION OF H₂

Hydrogen is mainly used in various syntheses as an alternative fuel. Once it was used as filling gas for balloons, and recently also as an energy source in fuel cells.

PACKAGING

Hydrogen is delivered in the following packaging units:

- in bulk

IDENTIFICATION OF THE PRODUCT

Trade name: HYDROGEN, gas
Substance name: HYDROGEN
IUPAC name: HYDROGEN
Molecular formula: H₂
Molecular Mass: 1 g/mol
CAS No.: 1333-74-0
EI NECS No.: 215-605-7

DEMINERALISED WATER (DMW) - H₂O

IDENTIFICATION OF THE PRODUCT

Trade name: DEMINERALISED WATER
Substance name: WATER
IUPAC name: WATER
Molecular formula: H₂O
Molecular Mass: 18 g/mol
CAS No.: 7732-18-5
EI NECS No.: 231-791-2

DESCRIPTION

Belinka Perkemija produces demineralized water of high quality - under 0.05 µS.

APPLICATION OF DMW

Demineralized water has a very wide range of applications

PACKAGING

Demineralized water is delivered in the following packaging units:

- in bulk



MORE INFORMATION

There are more data available in TDS (technical data sheet), specifications and advices regarding products issued by Belinka Perkemija.

Additional information relating to dangerous and physical-chemical properties, and other information that affect the safe use and handling of the product, can be found on the safety data sheet.

For additional information, please contact our Technical Service Team, phone +386 1 5886 330; e-mail: perkemija@belinka.si.



belinka perkemija

Belinka Perkemija, d.o.o.
Zasavska cesta 95
1231 Ljubljana-Črnuče
Slovenija (SI)
www.belinka-perkemija.com

A member of the European Helios Group.

More information and general terms available at www.belinka-perkemija.com.